



## Reinforced Concrete Pipe / Tongue and Groove Joint 12" - 96" Diameter







**Section Thru Barrel** 

**Section Thru Joint** 

Table of Pipe Properties					
	B-Wall		C-Wall		
Pipe Inside	Wall	Approx.	Wall	Approx.	Waterway
Diameter	Thickness	Weight	Thickness	Weight	Area
(inches)	(inches)	(lbs/ft)	(inches)	(lbs/ft)	(ft <sup>2</sup> )
12	2	92	2-3/4	133	0.79
15	2-1/4	127	3	177	1.23
18	2-1/2	168	3-1/4	226	1.77
21	2-3/4	214	3-1/2	281	2.41
24	3	265	3-3/4	341	3.14
30	3-1/2	384	4-1/4	476	4.91
36	4	524	4-3/4	633	7.07
42	4-1/2	685	5-1/4	812	9.62
48	5	867	5-3/4	1,011	12.6
54	5-1/2	1,071	6-1/4	1,232	15.9
60	6	1,296	6-3/4	1,474	19.6
66	6-1/2	1,542	7-1/4	1,738	23.8
72	7	1,810	7-3/4	2,023	28.3
78	7-1/2	2,098	8-1/4	2,329	33.2
84	8	2,409	8-3/4	2,656	38.5
90	8-1/2	2,740	9-1/4	3,004	44.2
96	9	3,093	9-3/4	3,374	50.3

## Notes

1. Pipe manufactured to meet current ASTM and AASHTO specifications.

## **Disclaimer**:

The product information contained in this document is believed to be accurate. Please note that not all products are made at all our facilities. For more information, specifics, and product availability, please contact your local sales representative.

©2023 Rinker Materials Rinker 001 - 03/2023